

TT-FLAT PROBE

Ordering information	Catalog Number	P/N	Description
	TT-FLAT PROBE	P000001074	Water leak detection probe

Product Characteristics		
Dimensions	4.7 in L x 3.8 in W x 1.3 in H (120 mm L x 98 mm W x 32 mm H)	
Weight	0.4 lb nominal	
Shroud	Epoxy coated aluminum, orange	
Probes	316 Stainless steel	
Probe height above mounting surface	Adjustable	
Housing	Black PVC	
Maximum ambient temperature	122°F (50°C)	
Minimum ambient temperature	32°F (0°C)	
Connections	4-wire TraceTek jumper cable to terminal strip	
Minimum water depth to trigger leak	0.2 in (5 mm) on metal surface*	
Minimum water depth to trigger leak	0.5 in (12.7 mm) on insulating surface*	

*With sensor tip height close to mounting surface but not touching

Tyco and TraceTek are trademarks of Tyco Thermal Controls LLC or its affiliates.

Worldwide Headquarters
Tyco Thermal Controls
 307 Constitution Drive
 Menlo Park, CA 94025-1164
 USA
 Tel (800) 545-6258
 Tel (650) 216-1526
 Fax (800) 527-5703
 Fax (650) 474-7215
 info@tracetek.com
 www.tracetek.com

Important: All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their particular application. Tyco Thermal Controls makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. Tyco Thermal Controls' only obligations are those in the Tyco Thermal Controls Standard Terms and Conditions of Sale for this product, and in no case will Tyco Thermal Controls or its distributors be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of the product. Specifications are subject to change without notice. In addition, Tyco Thermal Controls reserves the right to make changes—without notification to Buyer—to processing or materials that do not affect compliance with any applicable specification.